























PASSUM UP





Ø mm	Cassaforma In-ground box	Corpo - Light body Optica - Optic	W	IK	Fascio luminoso Angle beam	Driver	T ^v Vetro Glass	Carico Load pressure Kg	Calp/ carrabile Walk/drive over	Flange Flanges	Antiscivolo Skidproof
70	 ø 105 x 90	 Alluminio Aluminium INOX Stainless Steel Fisso - Fix	1/3 LED	8	18°/38°/90°	OUT	≤40°	1000		Alluminio Aluminium INOX Stainless Steel	-
125	 ø 230 x 115	 Alluminio Aluminium INOX Stainless Steel Basculante Adjustable	6,5* LED	10	18°/38°/90°	IN	≤40°	2000		Alluminio Aluminium INOX Stainless Steel	-
			4 LED	10	18°/38°/90°	IN	≤40°	2000			
			5 GU 10	10	18°/38°/90°	IN	≤40°	2000			
125 ultraflat	 ø 160 x 70	 Alluminio - Aluminium Fisso - Fix	8 LED	10	90°	IN	≤40°	2000		Alluminio Aluminium INOX Stainless Steel	-
180	 ø 300 x 135	 Alluminio Aluminium INOX Stainless Steel Basculante Adjustable	15* LED	10	18°/38°/90°	IN	≤40°	3500		Alluminio Aluminium INOX Stainless Steel	OPTION
			9,5/6,5 LED	10	18°/38°/90°	IN	≤40°	3500			
			7-8 GU 10	10	18°/38°/90°	IN	≤40°	3500			
245	 ø 360 x 286,8	 Alluminio - Aluminium Basculante Adjustable	29 LED	10	18°/38°/90°	IN	≤40°	3500		Alluminio Aluminium INOX Stainless Steel	OPTION
			70 Ioduri Metallici Metal Halide	10	18°/38°	IN	≤40°	3500			
			30 E27	10	90°	IN	≤40°	3500			
245 RGB W	 ø 360 x 286,8	 Alluminio - Aluminium Basculante Adjustable	20 LED	10	40°	IN	≤40°	3500		Alluminio Aluminium INOX Stainless Steel	OPTION

* Solo Alluminio - Aluminium only

PASSUM SIDEWARDS

Ø mm	Cassaforma In-ground box	Corpo - Light body Optica - Optic	Sporgenza Canopy height mm	W	IK	Driver	T ^v Vetro Glass	Carico Load pressure Kg	Calp/ carrabile Walk/drive over	Calotte Canopies
70	 ø 105 x 90	 Alluminio Aluminium INOX Stainless Steel Fisso - Fix	20,5	1/3 LED	8	OUT	≤40°	2000		Alluminio - Aluminium INOX - Stainless Steel
125	 ø 230 x 115	 Alluminio Aluminium INOX Stainless Steel Fisso - Fix	32	4 LED	10	IN	≤40°	2000		Alluminio - Aluminium
180	 ø 300 x 135	 Alluminio Aluminium INOX Stainless Steel Fisso - Fix	33	9,5 LED	10	IN	≤40°	2000		Alluminio - Aluminium

PASSUM orientabile/adjustable

Ø mm	Cassaforma In-ground box	Corpo - Light body Optica - Optic	Sporgenza Canopy height mm	W	IK	Driver	T ^v Vetro Glass	Carico Load pressure Kg	Calp/ carrabile Walk/drive over	Fascio luminoso / inclinazione Angle beam / oriented
180	 ø 300 x 135	 Alluminio Aluminium INOX Stainless Steel Orientabile Adjustable	43	8 LED	10	IN	≤40°	2000		

PASSUM DRIVERS

ALIMENTATORI 24V DC PER COLLEGAMENTO IN PARALLELO
24V DC DRIVER FOR PARALLEL CONNECTION

CODE	Volt DC	W	IP	Dimensioni - Dimensions mm
1952	24	18	67	140 x 30 x 22
1954	24	35	67	148 x 40 x 30
1955	24	60	67	162.5 x 42.5 x 32