




Pole complete with luminaire

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Light source: mains voltage LED module, compatible with phase-cut dimmers

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

Dimensions	128 x 44 x H 600 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	368 lm
System output	210 lm
System efficiency	53 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	2.2 kg
Conformity	CE UK CA

CODE OPTIONS


FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

ACCESSORIES



STAMP THE SERIES

