




Pole complete with 2 luminaires

Material: aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Built-in phase-cut dimmable drivers

Light source: LED unit

Supplied with two H05RN-F pre-wired cables (optional waterproof connections to be ordered separately)

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

S Version with sensor

D* Dimmable version

LV 24÷48V low voltage

Dimensions	193 x 90 x H 600 mm
Light source	LED
Wattage	16 W
Power supply	220-240 V 50/60 Hz
Light source output	2154 lm
System output	1040 lm
System efficiency	65 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	5 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

ACCESSORIES



STAMP

THE SERIES

