
ACCESSORIES WATERPROOF CONNECTOR

1944





Up to 4 outputs joint connector 3x2,5 mm², based on two-component silicone gel

Dimensions	95 x 44 x 24 mm
IP rating	IP 68
Weight	0,1 kg
Conformity	CE UK CA

ACCESSORIES WATERPROOF CONNECTOR

1944

FIXTURES RELATED

CLOCK
80

4661

STAMP POST
SLIM H 300

5371

STAMP POST
SLIM H 600

5372

STAMP POST
H 600 1X

5381

STAMP POST
H 900 1X

5382

STAMP POST
H 600 2X

5383

STAMP POST
H 900 2X

5384

STAMP POST GLASS
H 300

5374

STAMP POST GLASS
H 600

5375

CLOCK
120

4664

CLOCK
120

4665

PASSUM UP
Ø 125 ALUMINIUM

1422

PASSUM UP
Ø 125 ALUMINIUM

1424

PASSUM SIDEWARDS
Ø 125 ALUMINIUM

1427

PASSUM UP
Ø 125 STAINLESS STEEL

1495

PASSUM SIDEWARDS
Ø 125 STAINLESS STEEL

1485

PASSUM UP
Ø 125 STAINLESS STEEL

1496

PASSUM SIDEWARDS
Ø 180 ALUMINIUM

1436

PASSUM SPOT
Ø 180 ALUMINIUM

1438

PASSUM SIDEWARDS
Ø 180 STAINLESS STEEL

1487

PASSUM UP
Ø 180 ALUMINIUM

1432

PASSUM UP
Ø 180 ALUMINIUM

1433

PASSUM UP
Ø 180 ALUMINIUM

1434

PASSUM UP
Ø 180 STAINLESS STEEL

1497

ACCESSORIES WATERPROOF CONNECTOR

1944

PASSUM UP
Ø 180 STAINLESS STEEL



1498

PASSUM UP
Ø 245 ALUMINIUM



1440

PASSUM UP
Ø 245 ALUMINIUM



1442

PASSUM DOWNLIGHT
Ø 125



1472

PASSUM DOWNLIGHT
Ø 125



1473

PASSUM UP
Ø 245 ALUMINIUM



1444

PASSUM DOWNLIGHT
Ø 125 ULTRAFLAT



1479

PASSUM DOWNLIGHT
Ø 180



1474

PASSUM DOWNLIGHT
Ø 180



1475

PASSUM DOWNLIGHT
Ø 245



1471

PASSUM DOWNLIGHT
Ø 245



1476

PASSUM DOWNLIGHT
Ø 245



1478

PASSUM SPOT
Ø 180 STAINLESS STEEL + ALUMINIUM COVER



1488

PASSUM ASYMMETRIC
Ø 180 ALUMINIUM



1439

PASSUM ASYMMETRIC
Ø 245 ALUMINIUM



1449

VOID POST
H 300



1352

VOID POST
H 600



1353