
ACCESSORIES WATERPROOF CONNECTOR

1942





Joint connector for through wiring (3x2,5 mm² cables)

Dimensions	130 x 63 x 33 mm
IP rating	IP 68
Weight	0.08 kg
Conformity	CE UKCA

ACCESSORIES WATERPROOF CONNECTOR

1942

FIXTURES RELATED

CLOCK
80

4661

STANDING

5526

CLOCK
120

4664

CLOCK
120

4665

PASSUM UP
Ø 125 ALUMINIUM

1422

PASSUM UP
Ø 125 ALUMINIUM

1424

PASSUM UP
Ø 125 STAINLESS STEEL

1495

PASSUM SIDEWARDS
Ø 125 ALUMINIUM

1427

PASSUM SIDEWARDS
Ø 125 STAINLESS STEEL

1485

PASSUM UP
Ø 125 STAINLESS STEEL

1496

PASSUM SIDEWARDS
Ø 180 ALUMINIUM

1436

PASSUM SPOT
Ø 180 ALUMINIUM

1438

PASSUM SIDEWARDS
Ø 180 STAINLESS STEEL

1487

PASSUM UP
Ø 180 ALUMINIUM

1432

PASSUM UP
Ø 180 ALUMINIUM

1433

PASSUM UP
Ø 180 ALUMINIUM

1434

PASSUM UP
Ø 180 STAINLESS STEEL

1497

PASSUM UP
Ø 180 STAINLESS STEEL

1498

PASSUM UP
Ø 245 ALUMINIUM

1440

PASSUM UP
Ø 245 ALUMINIUM

1442

PASSUM DOWNLIGHT
Ø 125

1472

PASSUM UP
Ø 245 ALUMINIUM

1444

PASSUM DOWNLIGHT
Ø 125

1473

PASSUM DOWNLIGHT
Ø 125 ULTRAFLAT

1479

ACCESSORIES WATERPROOF CONNECTOR

1942

PASSUM DOWNLIGHT
Ø 180



1474

PASSUM DOWNLIGHT
Ø 180



1475

PASSUM DOWNLIGHT
Ø 245



1471

PASSUM DOWNLIGHT
Ø 245



1476

PASSUM DOWNLIGHT
Ø 245



1478

PASSUM SPOT
Ø 180 STAINLESS STEEL + ALUMINIUM COVER



1488

PASSUM ASYMMETRIC
Ø 180 ALUMINIUM



1439

PASSUM ASYMMETRIC
Ø 245 ALUMINIUM



1449

VOID POST
H 300



1352

VOID POST
H 600



1353