



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D* Dimmable version

| | |
|------------------------------------------|----------------------|
| Dimensions | Ø 268 x 118 mm |
| Light source | LED |
| Wattage | 15 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 2308 lm |
| System output | 600 lm |
| System efficiency | 40 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | C |
| LED lifetime | L70 B50 102.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class I |
| IP rating | IP 66 |
| Impact resistance rating | IK 10 (20 joules) |
| Norms | EN 60598-1 +2-1 |
| Weight | 1.36 kg |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

| | |
|-----------|----------------|
| AG | ALUMINIUM GREY |
| AN | ANTHRACITE |
| BI | WHITE |

COLOUR TEMP.

| | |
|------------|-------|
| 27K | 2700K |
| 3K | 3000K |
| 4K | 4000K |