



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D\*** Dimmable version

Dimensions	Ø 268 x 129 mm
Light source	LED
Wattage	15 W
Power supply	220-240 V   50/60 Hz
Light source output	2300 lm
System output	298 lm
System efficiency	20 lm/W
Color Rendering Index – CRI	80
LED energy class	C
LED lifetime	L70 B50 72.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	2.1 kg
Conformity	CE UK CA

### CODE OPTIONS

#### FINISH

<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>BI</b>	WHITE

#### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K