
goccia ILLUMINAZIONE

K³ MINILED 1x LED 1X3W 1X70°

1041





Outdoor luminaire for wall installation

Material: low copper content die-cast aluminium

UV resistant polycarbonate diffuser, flush with the frame

Built-in driver

Light source: LED unit

Rear cable entry

Color matching stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D* Dimmable version

Dimensions	100 x 100 x 102 mm
Light source	LED
Wattage	3 W
Power supply	100-240 V | 50/60 Hz
Light source output	300 lm
System output	200 lm
System efficiency	67 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (2700K), D (3000K)
LED lifetime	L70 B50 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 / -2-1
Weight	1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BI	WHITE

on request:

CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

goccia ILLUMINAZIONE

Goccia Illuminazione srl
via E.Fermi 59/65 - 25020 Poncarale (BS) Italy
+39 030 2640761 - info@www.goccia.it

IMQ CERTIFIED QUALITY MANAGEMENT SYSTEM ISO 9001:2015

IQNET RECOGNIZED CERTIFICATION

K³ MINILED 1x LED 1X3W 1X70°

1041

ACCESSORIES

K³ MINILED
SPIKE

NO IMAGE AVAILABLE

1090

K³ MINILED THE SERIES