

Outdoor luminaire for wall installation
Material: low copper content die-cast aluminium
UV resistant polycarbonate diffuser, flush with the frame
Built-in driver
Light source: LED unit
Rear cable entry
Color matching stainless steel Allen screws
Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D* Dimmable version

15 Optic 15°

Dimensions	100 x 100 x 102 mm
Light source	LED
Multiple sources	2x
Wattage	6 W
Power supply	100-240 V 50/60 Hz
Light source output	600 lm
System output	72 lm
System efficiency	12 lm/W
Color Rendering Index – CRI	80
LED energy class	C (4000K), D (2700K), D (3000K)
LED lifetime	L70 B50 > 60.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class II
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE


COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

on request:



ACCESSORIES



K³ MINILED

THE SERIES

