

Outdoor luminaire for wall installation

Material: low copper content die-cast aluminium

UV resistant polycarbonate diffuser, flush with the frame

Built-in driver

Light source: LED unit

Rear cable entry

Color matching stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D\*** Dimmable version

|                                          |                                        |
|------------------------------------------|----------------------------------------|
| Dimensions                               | <b>100 x 100 x 102 mm</b>              |
| Light source                             | <b>LED</b>                             |
| Multiple sources                         | <b>4x</b>                              |
| Wattage                                  | <b>12 W</b>                            |
| Power supply                             | <b>100-240 V   50/60 Hz</b>            |
| Light source output                      | <b>1200 lm</b>                         |
| System output                            | <b>800 lm</b>                          |
| System efficiency                        | <b>67 lm/W</b>                         |
| Color Rendering Index – CRI              | <b>80</b>                              |
| LED energy class                         | <b>C (4000K), D (2700K), D (3000K)</b> |
| LED lifetime                             | <b>L70 B50 &gt; 60.000 h</b>           |
| Standard Deviation Color Matching (SDCM) | <b>MacAdam step 3</b>                  |
| Electrical insulation class              | <b>Class II</b>                        |
| IP rating                                | <b>IP 65</b>                           |
| Impact resistance rating                 | <b>IK 10 (20 joules)</b>               |
| Norms                                    | <b>EN 60598-1 +2-1</b>                 |
| Weight                                   | <b>0.98 kg</b>                         |
| Conformity                               | <b>CE UK CA</b>                        |

## CODE OPTIONS

### FINISH

|           |                |
|-----------|----------------|
| <b>AG</b> | ALUMINIUM GREY |
| <b>AN</b> | ANTHRACITE     |
| <b>BI</b> | WHITE          |


### COLOUR TEMP.

|            |       |
|------------|-------|
| <b>27K</b> | 2700K |
| <b>3K</b>  | 3000K |
| <b>4K</b>  | 4000K |

on request:



ACCESSORIES



**K<sup>3</sup> MINILED**

THE SERIES

