



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D* Dimmable version

Dimensions	Ø 260 x 171 mm
Light source	LED
Wattage	15 W
Power supply	220-240 V 50/60 Hz
Light source output	2308 lm
System output	645 lm
System efficiency	43 lm/W
Color Rendering Index – CRI	80
LED energy class	C
LED lifetime	L70 B50 102.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.6 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BI	WHITE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

KASKO Ø 260 with guard - vandalproof LED 15W VANDALPROOF 9164



KASKO

THE SERIES

