
PASSUM UP Ø 125 stainless steel GU10 5W

1496





Outdoor ground/wall recessed luminaire

Max. load pressure 2.000 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: AISI 316L stainless steel

Diffuser: ultra-white transparent tempered glass

Driver not necessary

Luminaire supplied without light source

Adjustable optic ±8°

Pre-wired with 0,5 m H07RN-F buriable cable (optional waterproof connections to be ordered separately)

On request versions (additional code):

LV low voltage 12÷24V / 24÷48V / 10÷52V

Dimensions	Ø 107 x H 112 mm
Light source	GU10
Light source info	L < 57 mm
Wattage	5 W
Power supply	220-240 V | 50/60 Hz
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Diffuser contact temperature	≤ 40°C
Norms	EN 60598-1 / -2-13
Weight	0.62 kg
Conformity	CE UK CA

Goccia Illuminazione srl
via E.Fermi 59/65 - 25020 Poncarale (BS) Italy
+39 030 2640761 - info@www.goccia.it

PASSUM UP Ø 125 stainless steel GU10 5W

1496

COMPONENTS

PASSUM
Ø 125 IN-GROUND BOX



1421

PASSUM UP
Ø 125 STAINLESS STEEL ROUND FLANGE



1522

PASSUM UP
Ø 125 STAINLESS STEEL SQUARE FLANGE



1523

ACCESSORIES

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR



1944

ACCESSORIES
WATERPROOF CONNECTOR



1942

PASSUM UP THE SERIES







