
STAMP SIDELIGHT 4x LED 8W (4X2W)

5337





Outdoor wall steplight luminaire with minimum thickness for surface installation

Material: low copper content die-cast aluminium

Diffuser: UV resistant polycarbonate

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear single cable entry / Spacer optional accessory for side cable entry

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

Dimensions	120 x 120 x 26 mm
Light source	LED
Multiple sources	4x
Wattage	8 W
Power supply	220-240 V | 50/60 Hz
Light source output	764 lm
System output	500 lm
System efficiency	63 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 / -2-1
Weight	0.43 kg
Conformity	CE UKCA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BI	WHITE

on request:

CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

Goccia Illuminazione srl
via E.Fermi 59/65 - 25020 Poncarale (BS) Italy
+39 030 2640761 - info@www.goccia.it

STAMP SIDELIGHT 4x LED 8W (4X2W)

5337

ACCESSORIES

STAMP
SPACER



5351

STAMP
FIXING BRACKET



5360

STAMP THE SERIES





