



Parallelepiped-shaped garden post with downward front light, protected by an antidazzle louvre, designed for lighting walkways and paths

The structure allows to insert a second luminaire with diffused light on the lower back

Material: low copper content die-cast aluminium

Light source: mains voltage LED module, compatible with phase-cut dimmers

Watertight single or through wiring connection by optional watertight connectors to be ordered separately

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D* Dimmable version

Dimensions	86 x 73 x H 495 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	835 lm
System output	423 lm
System efficiency	53 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F (3000K), F (4000K), G (2700K)
LED lifetime	L70 B10 > 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	2 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

STANDING LED 8W 5526



ACCESSORIES

ACCESSORIES WATERPROOF CONNECTOR  1941	ACCESSORIES WATERPROOF CONNECTOR  1942	ACCESSORIES GROUND ANCHORS  5529	STANDING BACKLIGHT  5528
--	--	--	--

STANDING

THE SERIES

