



Outdoor ground/wall recessed luminaire

Material: housing and closing cap in anodized anticorrosive turned aluminium for OS and ON finishes; housing in anodized anticorrosive turned aluminum and closing cap in AISI 316L stainless steel for IN finish

Diffuser: UV resistant polycarbonate

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED module

Side emitter optic to direct the light laterally

Supplied with 1,5 m cable

Finish: anodization for OS and ON versions; satin finish for IN version

On request versions (additional code):

**MT7** 7 m cable length

Dimensions	<b>Ø 60 x H 97 x H1 20 mm</b>
Light source	<b>LED</b>
Wattage	<b>5 W</b>
Power supply	<b>24 Vdc</b>
Light source output	<b>520 lm</b>
System output	<b>270 lm</b>
System efficiency	<b>54 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E (3000K), E (4000K), F (2700K)</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class III</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-13</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION  
**IN** STAINLESS STEEL

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K