



Outdoor luminaire for wall installation

Material: extruded aluminium body / Frames with flush diffuser /
Wall support in low copper content die-cast aluminium

Diffuser: clear polycarbonate, flush with the structure

Built-in driver

Light source: LED unit

Rear cable entry

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

Dimensions	Ø 60 x H 205 x 110 mm
Light source	LED
Multiple sources	2x
Power	8 W
Voltage/Frequency	100-240 V 50/60 Hz
Light source output	860 lm
System output	710 lm
System efficiency	89 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
BI	WHITE

on request:

CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	30°
optional optics	
10	10°
54	54°