



Outdoor luminaire for wall installation  
 Material: low copper content die-cast aluminium  
 Photo-etched polycarbonate diffuser to grant a homogeneous effect with diffused light  
 Built-in driver  
 Light source: LED unit  
 Rear cable entry  
 Stainless steel screws  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D\* Dimmable version
- LV 24÷48V low voltage

Dimensions	<b>217 x 106 x 46 mm</b>
Light source	<b>LED</b>
Wattage	<b>9 W</b>
Power supply	<b>100-240 V   50/60 Hz</b>
Light source output	<b>1077 lm</b>
System output	<b>745 lm</b>
System efficiency	<b>83 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>F</b>
LED lifetime	<b>L70 B50 &gt; 50.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 66</b>
Impact resistance rating	<b>IK 07 (2 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>0.98 kg</b>
Conformity	<b>CE UK CA</b>

### CODE OPTIONS

FINISH	COLOUR TEMP.	OPTIC
<b>AG</b> ALUMINIUM GREY	<b>27K</b> 2700K	
<b>AN</b> ANTHRACITE	<b>3K</b> 3000K	
<b>CO</b> CORTEN	<b>4K</b> 4000K	
<b>BR</b> BRONZE		
<b>BI</b> WHITE		