



Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 Ultra-white transparent tempered glass flush diffuser
 Light source: mains voltage LED module, compatible with phase-cut dimmers
 Rear cable entry
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D* Dimmable version
- **+** Independent up+down optics

Dimensions	53 x 74 x H 85 mm
Light source	LED
Multiple sources	2x
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	760 lm
System output	596 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B10 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE
 BI WHITE

on request:

AG ALUMINIUM GREY
 CO CORTEN
 BR BRONZE

COLOUR TEMP.

27K 2700K
 3K 3000K
 4K 4000K

OPTIC

standard 30°

optional optics

17 17°
 54 54°