


K³ MIKRO POST H 200 1x50° LED 4W 1025



Pole complete with luminaire

Material: aluminium

Ultra-white transparent tempered glass diffuser, flush with the structure and black silk-screened

Light source: mains voltage LED module, compatible with phase-cut dimmers

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

24V 24V low voltage

Dimensions	60 x 60 x H 200 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	380 lm
System output	35 lm
System efficiency	9 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B10 > 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE
CO CORTEN
BR BRONZE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K