LATO 750 LED 13W

7202





Pole complete with luminaire

Material: low copper content die-cast aluminium luminaire / Extruded aluminium pole / Stainless steel base

Diffuser: clear polycarbonate

Built-in driver

Light source: linear LED module

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the luminaire

Optional surge protection device (SPD) to be ordered separately

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D* Dimmable version

Dimensions	217 x 132 x H 750 mm
Light source	LED
Wattage	13 W
Power supply	220-240 V | 50/60 Hz
Light source output	1500 lm
System output	934 lm
System efficiency	72 lm/W
Color Rendering Index – CRI	80
LED energy class	D
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 / -2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AG	ALUMINIUM GREY
AN	ANTHRACITE
CO	CORTEN
BR	BRONZE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

LATO 750 LED 13W

7202

ACCESSORIES

ACCESSORIES
SPD



1965

ACCESSORIES
ANCHOR PLATE



1358