



Outdoor luminaire for ceiling installation

Material: low copper content die-cast aluminium

Ultra-white transparent tempered glass diffuser, flush with the structure and black silk-screened

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):  
24V 24V low voltage

Dimensions	<b>60 x 60 x H 75 mm</b>
Light source	<b>LED</b>
Wattage	<b>4 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>380 lm</b>
System output	<b>298 lm</b>
System efficiency	<b>75 lm/W</b>
Color Rendering Index – CRI	<b>≥80</b>
LED energy class	<b>F</b>
LED lifetime	<b>L70 B10 45.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 65</b>
Impact resistance rating	<b>IK 10 (20 joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>CO</b>	CORTEN
<b>BR</b>	BRONZE
<b>BI</b>	WHITE

### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K

### OPTIC

<b>standard</b>	30°
optional optics	
<b>17</b>	17°
<b>54</b>	54°