



Outdoor luminaire for ceiling installation

Material: low copper content die-cast aluminium

Ultra-white transparent tempered glass diffuser, flush with the structure and black silk-screened

Light source: mains voltage LED module, compatible with phase-cut dimmers

Rear cable entry

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
24V 24V low voltage

Dimensions	60 x 60 x H 75 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	380 lm
System output	298 lm
System efficiency	75 lm/W
Color Rendering Index – CRI	≥80
LED energy class	F
LED lifetime	L70 B10 > 45.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.38 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.		OPTIC	
AG	ALUMINIUM GREY	27K	2700K	standard	30°
AN	ANTHRACITE	3K	3000K	optional optics	
CO	CORTEN	4K	4000K	17	17°
BR	BRONZE			54	54°
BI	WHITE				