
goccia ILLUMINAZIONE

RUNNER M LED 35W

1772





Outdoor ground recessed luminaire

Max. load pressure 1.300 kg for walk-over use

Material: AISI 316L stainless steel rectangular flange / Extruded aluminium housing / Side covers in low copper content die-cast aluminium alloy 44300

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: highly performing LED module

Dedicated optics / Matt black louvre for maximum visual comfort

Watertight wiring with 1 m cable / Predisposition for through wiring, on request

Stainless steel Allen screws

Satin finish

On request versions (additional code):

A2	Optional shield
D*	Dimmable version
48V	48V low voltage
I/O	Through wiring

Dimensions	630 x 99 x 85 mm
Light source	LED
Wattage	35 W
Power supply	220-240 V | 50/60 Hz
Light source output	3878 lm
System output	2058 lm
System efficiency	59 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L95 B05 > 90.700 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 / -2-13
Conformity	CE UK CA

CODE OPTIONS

FINISH

IN	STAINLESS STEEL

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	20° WALL GRAZER

optional optics

10	10° NARROW
30	30° MEDIUM
55	55° WIDE
83	83° EXTRA-WIDE
WW	WALL WASHER
EL	ELLIPTICAL

RUNNER M LED 35W

1772

COMPONENTS

RUNNER
M IN-GROUND BOX



1762