



Outdoor luminaire for wall installation

Material: stainless steel rectangular flange / Extruded aluminium housing / Side covers in low copper content die-cast aluminium alloy 44300 / Aluminium adjustable fixing brackets

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: highly performing LED module

Dedicated optics / Matt black louvre for maximum visual comfort

Watertight wiring with 1 m cable / Predisposition for through wiring, on request

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

L Brackets 174 mm (overall dimension 246 mm)

A2 Optional shield

D* Dimmable version

48V 48V low voltage

I/O Through wiring

Dimensions	304 x 140 x 85 mm
Light source	LED
Wattage	18 W
Power supply	220-240 V 50/60 Hz
Light source output	1939 lm
System output	1029 lm
System efficiency	57 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L95 B05 > 90.700 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE

COLOUR TEMP.

27K 2700K

3K 3000K

4K 4000K

OPTIC

standard 20° WALL GRAZER

optional optics

10 10° NARROW

30 30° MEDIUM

55 55° WIDE

83 83° EXTRA-WIDE

WW WALL WASHER

EL ELLIPTICAL