goccia ILLUMINAZIONE

CLIMBER M LED 35W

1782





Outdoor luminaire for wall installation

Material: stainless steel rectangular flange / Extruded aluminium housing / Side covers in low copper content die-cast aluminium alloy 44300 / Aluminium adjustable fixing brackets

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: highly performing LED module

Dedicated optics / Matt black louvre for maximum visual comfort

Watertight wiring with 1 m cable / Predisposition for through wiring, on request

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

L	Brackets 174 mm (overall dimension 246 mm)
A2	Optional shield
D*	Dimmable version
48V	48V low voltage
I/O	Through wiring

Dimensions	584 x 140 x 85 mm
Light source	LED
Wattage	35 W
Power supply	220-240 V | 50/60 Hz
Light source output	3878 lm
System output	2058 lm
System efficiency	59 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (4000K), F (2700K), F (3000K)
LED lifetime	L95 B05 > 90.700 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 / -2-1
Weight	4.6 kg
Conformity	CE UKCA

CODE OPTIONS

FINISH

AN	ANTHRACITE

COLOUR TEMP.

27K	2700K
3K	3000K
4K	4000K

OPTIC

standard	20° WALL GRAZER

optional optics

10	10° NARROW
30	30° MEDIUM
55	55° WIDE
83	83° EXTRA-WIDE
WW	WALL WASHER
EL	ELLIPTICAL