
PASSUM UP RGBW Ø 245 ALUMINIUM LED RGBW 32W MAX

1482





Outdoor ground recessed luminaire

Max. load pressure 3.500 kg (in-ground box + luminaire + covering flange together for drive-over use)

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: 3 RGBW LEDs and a device to receive DMX standard 512 signal sent from the control unit 1181 or another compatible unit

Adjustable optics ±25°

Supplied with two 0,5 m cables: signal + 230V power supply

Up to 32 luminaires can be connected to each control unit

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
** Multi-channel setting

Dimensions	Ø 218 x H 266 mm
Light source	LED RGBW (W = 3000K)
Wattage	max 32 W
Power supply	100-240 V | 50/60 Hz
Light source output	990 lm
System output	690 lm
System efficiency	22 lm/W
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 / -2-13
Weight	3.3 kg
Conformity	CE UK CA

CODE OPTIONS

OPTIC

standard	30°

optional optics

10	10°
54	54°

PASSUM UP RGBW Ø 245 ALUMINIUM LED RGBW 32W MAX

1482

COMPONENTS

PASSUM
Ø 245 IN-GROUND BOX



1441

PASSUM UP
Ø 245 ALUMINIUM ROUND FLANGE



1541

PASSUM UP
Ø 245 STAINLESS STEEL ROUND FLANGE



1542

ACCESSORIES

ACCESSORIES
SIGNAL GENERATOR



1181

ACCESSORIES
24V DRIVER – 60W



1925

ACCESSORIES
24V DRIVER – 150W



1926