



Outdoor wall steplight luminaire

Minimum thickness for surface installation / Recessed installation flush with the wall using backbox optional accessory

Material: low copper content die-cast aluminium

UV resistant polycarbonate diffuser, recessed for an effective reduction of direct glare

Built-in driver

Light source: LED unit

Rear cable entry / Through wiring allowed

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- LV 24÷48V low voltage

Dimensions	280 x 150 x 31 mm
Light source	LED
Wattage	16 W
Power supply	220-240 V 50/60 Hz
Light source output	2345 lm
System output	936 lm
System efficiency	59 lm/W
Color Rendering Index – CRI	≥80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	1.44 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

- AG** ALUMINIUM GREY
- AN** ANTHRACITE
- CO** CORTEN
- BR** BRONZE
- BI** WHITE

COLOUR TEMP.

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K

ACCESSORIES



STAMP THE SERIES

